

# B-MAX4 II

## SETTING SHEET Ver.03

CIRCUIT

EOS Rd.4 Wels, Austria

- INDOOR ○ OUTDOOR
- WET ○ DRY ○ DUSTY ● OTHER
- LOW TRACTION ● MED TRACTION ○ HIGH TRACTION
- SMOOTH ○ BUMPY ○ BLUE GROOVE ○ ASTROTURF
- CARPET ○ WOOD

DRIVER N.Matsukura

DATE 2014/04/27

FRONT

0 mm  
2 mm  
1 mm  
17 mm

◆CAMBER  
● ← ○ 2.5 °

◆TOE ○ IN ● OUT 0.5 °

+1mm  
FF ○ ○ ○ ○ ○ ○  
FR ○ ○ ○ ○ ○ ○

○1.0 ○1.1  
○1.2 ○1.3  
○1.4

○ BALL DIFF  
● GEAR DIFF  
#10,000

19 mm

mm

**SPRING**  
● ORANGE  
○

**OIL**  
#550  
○ #1 ○ #2 ○ #3  
● 1.6x2 (BM-S162)  
○  
○  
1 mm x 3  
mm x

REAR

mm  
mm

1 mm

○0°  
○0.5°  
○1°

◆CAMBER  
● ← ○ 2.5 °

RF ○  
RF ○  
+0.5°

○1.0 ○1.1  
○1.2 ○1.3  
○1.4 ○1.5  
○1.6 ●1.8

○ BALL DIFF  
● GEAR DIFF  
#10,000

24.5 mm

mm

**SPRING**  
● GREEN  
○

**OIL**  
#400  
○ #1 ○ #2 ○ #3  
○ 1.6x2 (BM-S162)  
●  
○  
mm x  
mm x

B2-S2S Front shock shaft  
SD-008RC

DRIVE

2 mm

MOTOR ⇨ R.P. M series 5.5T (Proto) ○ Bonded  
○ Sintered mm


GEAR ⇨ Spur 84T / Pinion 19T : 2.35

BATTERY ⇨ YOKOMO

ESC ● Racing Performer X Series

○ BL-R3 ○

Battery placement



TIRE

**FRONT**

TIRE ⇨ PL

INSERTS ⇨ PL

WHEELS ⇨ B4-821

**REAR**

TIRE ⇨ PL

INSERTS ⇨ PL

WHEELS ⇨ B4-827

OTHER

○ FULL RIP

● YOKOMO PROTO

COMMENT

- B4-304MG Graphite center mount plate
- B4-TBS Titanium turnbuckle set
- B4-415R00 Aluminum rear hub career 0°
- B4-TSS Titanium screw set
- B2-S40 Shock bottom cap (with stepped collar)
- B4-200SS Graphite center link support