

YZF2DT SETTING SHEET Ver.01

CIRCUIT TRC Circuit

- INDOOR OUTDOOR
- WET DRY DUSTY OTHER
- LOW TRACTION MED TRACTION HIGH TRACTION
- SMOOTH BUMPY BLUE GROOVE ASTROTURF
- CARPET WOOD

DRIVER Team setup DATE 2016/03/30

FRONT

Flat Gull
 Z2-017D(Plastic)

1 mm
 2 mm
 Z2-300FU OS (Plastic)
 N (Plastic)
 Flat Gull
 Graphite
 Graphite
 Z2-415A
 Z2-300FLO
 Z2-300FL5
 B2-300FL(Steel)
 S (Plastic)

◆CAMBER ●↔○ 1 °
 ◆TOE ○IN ●OUT 0.5 °
 ◆RIDE HEIGHT 23 mm

2 mm
 2 mm
 4.3
 5.0
 2.0°
 5.5°

SPRING
 YELLOW (YS-A875)
 RED (YS-A850)

OIL
 # AE #30
 #1 #2 #3
 1.6mm×2(BM-S162)

22 mm
 SD-008RC

REAR

RF
 RR
 -0.5
 +0.5
 0-H1
 0-H2
 1-H3
 2-H4
 3-1H
 0-H1
 0-H2
 1-H3
 2-H4
 3-1H

◆CAMBER ●↔○ 1 °
 ◆RIDE HEIGHT 23 mm

2.5 mm
 3 mm
 0°
 0.5°
 1°
 5.0
 6.0
 0.5 mm
 S M L
 1 mm
 1 mm

Z2-300RUD
 Z2-008R

SPRING
 GREEN (YS-A1200)

OIL
 # AE #27.5
 #1 #2 #3
 1.6mm×2(BM-S162)

22 mm

DRIVE

MOTOR ⇨ Racing Performer M2 7.5T Rotor mm
 GEAR ⇨ Spur 80 T / Pinion 22 T : 2.6
 BATTERY ⇨ Racing Performer Ultra Li-po 7.4V 5000mAh (Shorty)
 ESC Racing Performer X Series

Battery placement

- 5mm × 1
- 10mm × 2
- 20mm × 1
- 5mm ×
- 10mm ×
- 20mm ×

OYT-RW25
 X

TIRE

FRONT
 TIRE ⇨ PL LP4リブ M3
 INSERTS ⇨ ノーマル
 WHEELS ⇨ B2-821HY

REAR
 TIRE ⇨ PL ホールショット M4
 INSERTS ⇨ ノーマル
 WHEELS ⇨ B-827

OTHER

COMMENT
 Z2-TSSD Z2-TBSD Z2-S2SD Z2-S2LD Z2-670VP
 B2-S821A
 PLフロントウイング使用
 モーターとギヤボックスの間に10g