

◆フロント一角 (単位 : 度) /Front Toe Angle (unit: degree)

| | | FF | | | | | | | | | | | | | | | | | | |
|----|---|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|
| | | A | | | | | | | | | | B | | | | | | | | |
| | | 39.5 | 39.9 | 40.3 | 40.7 | 41.1 | 41.5 | 41.9 | 42.3 | 42.7 | 43.5 | 43.9 | 44.3 | 44.7 | 45.1 | 45.5 | 45.9 | 46.3 | 46.7 | |
| FR | A | 39.5 | 0 | -0.3 | -0.6 | -0.9 | -1.1 | -1.4 | -1.7 | -2.0 | -2.3 | -2.9 | -3.1 | -3.4 | -3.7 | -4.0 | -4.3 | -4.6 | -4.9 | -5.1 |
| | | 39.9 | - | 0 | -0.3 | -0.6 | -0.9 | -1.1 | -1.4 | -1.7 | -2.0 | -2.6 | -2.9 | -3.1 | -3.4 | -3.7 | -4.0 | -4.3 | -4.6 | -4.9 |
| | | 40.3 | - | - | 0 | -0.3 | -0.6 | -0.9 | -1.1 | -1.4 | -1.7 | -2.3 | -2.6 | -2.9 | -3.1 | -3.4 | -3.7 | -4.0 | -4.3 | -4.6 |
| | | 40.7 | - | - | - | 0 | -0.3 | -0.6 | -0.9 | -1.1 | -1.4 | -2.0 | -2.3 | -2.6 | -2.9 | -3.1 | -3.4 | -3.7 | -4.0 | -4.3 |
| | | 41.1 | - | - | - | - | 0 | -0.3 | -0.6 | -0.9 | -1.1 | -1.7 | -2.0 | -2.3 | -2.6 | -2.9 | -3.1 | -3.4 | -3.7 | -4.0 |
| | | 41.5 | - | - | - | - | - | 0 | -0.3 | -0.6 | -0.9 | -1.4 | -1.7 | -2.0 | -2.3 | -2.6 | -2.9 | -3.1 | -3.4 | -3.7 |
| | | 41.9 | - | - | - | - | - | - | 0 | -0.3 | -0.6 | -1.1 | -1.4 | -1.7 | -2.0 | -2.3 | -2.6 | -2.9 | -3.1 | -3.4 |
| | | 42.3 | - | - | - | - | - | - | - | 0 | -0.3 | -0.9 | -1.1 | -1.4 | -1.7 | -2.0 | -2.3 | -2.6 | -2.9 | -3.1 |
| | | 42.7 | - | - | - | - | - | - | - | - | 0 | -0.6 | -0.9 | -1.1 | -1.4 | -1.7 | -2.0 | -2.3 | -2.6 | -2.9 |
| | | 43.5 | - | - | - | - | - | - | - | - | - | 0 | -0.3 | -0.6 | -0.9 | -1.1 | -1.4 | -1.7 | -2.0 | -2.3 |
| RR | B | 43.9 | - | - | - | - | - | - | - | - | - | - | 0 | -0.3 | -0.6 | -0.9 | -1.1 | -1.4 | -1.7 | -2.0 |
| | | 44.3 | - | - | - | - | - | - | - | - | - | - | - | 0 | -0.3 | -0.6 | -0.9 | -1.1 | -1.4 | -1.7 |
| | | 44.7 | - | - | - | - | - | - | - | - | - | - | - | - | 0 | -0.3 | -0.6 | -0.9 | -1.1 | -1.4 |
| | | 45.1 | - | - | - | - | - | - | - | - | - | - | - | - | - | 0 | -0.3 | -0.6 | -0.9 | -1.1 |
| | | 45.5 | - | - | - | - | - | - | - | - | - | - | - | - | - | - | 0 | -0.3 | -0.6 | -0.9 |
| | | 45.9 | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | 0 | -0.3 | -0.6 |
| | | 46.3 | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | 0 | -0.3 |
| | | 46.7 | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | 0 |

◆リア一角 (単位 : 度) /Rear Toe Angle (unit: degree)

| | | RF | | | | | | | | | | | | | | | | | | |
|----|---|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|---|
| | | B | | | | | | | | | | C | | | | | | | | |
| | | 43.5 | 43.9 | 44.3 | 44.7 | 45.1 | 45.5 | 45.9 | 46.3 | 46.7 | 46.4 | 46.8 | 47.2 | 47.6 | 48.0 | 48.4 | 48.8 | 49.2 | 49.6 | |
| RR | B | 43.5 | 0 | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | |
| | | 43.9 | 0.3 | 0 | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | |
| | | 44.3 | 0.5 | 0.3 | 0 | - | - | - | - | - | - | - | - | - | - | - | - | - | - | |
| | | 44.7 | 0.8 | 0.5 | 0.3 | 0 | - | - | - | - | - | - | - | - | - | - | - | - | - | |
| | | 45.1 | 1.1 | 0.8 | 0.5 | 0.3 | 0 | - | - | - | - | - | - | - | - | - | - | - | - | |
| | | 45.5 | 1.3 | 1.1 | 0.8 | 0.5 | 0.3 | 0 | - | - | - | - | - | - | - | - | - | - | - | |
| | | 45.9 | 1.6 | 1.3 | 1.1 | 0.8 | 0.5 | 0.3 | 0 | - | - | - | - | - | - | - | - | - | - | |
| | | 46.3 | 1.9 | 1.6 | 1.3 | 1.1 | 0.8 | 0.5 | 0.3 | 0 | - | - | - | - | - | - | - | - | - | |
| | | 46.7 | 2.1 | 1.9 | 1.6 | 1.3 | 1.1 | 0.8 | 0.5 | 0.3 | 0 | 0.2 | - | - | - | - | - | - | - | |
| | | 46.4 | 1.9 | 1.7 | 1.4 | 1.1 | 0.9 | 0.6 | 0.3 | 0.1 | - | 0 | - | - | - | - | - | - | - | |
| C | C | 46.8 | 2.2 | 1.9 | 1.7 | 1.4 | 1.1 | 0.9 | 0.6 | 0.3 | 0.1 | 0.3 | 0 | - | - | - | - | - | - | - |
| | | 47.2 | 2.5 | 2.2 | 1.9 | 1.7 | 1.4 | 1.1 | 0.9 | 0.6 | 0.3 | 0.5 | 0.3 | 0 | - | - | - | - | - | - |
| | | 47.6 | 2.7 | 2.5 | 2.2 | 1.9 | 1.7 | 1.4 | 1.1 | 0.9 | 0.6 | 0.8 | 0.5 | 0.3 | 0 | - | - | - | - | - |
| | | 48.0 | 3.0 | 2.7 | 2.5 | 2.2 | 1.9 | 1.7 | 1.4 | 1.1 | 0.9 | 1.1 | 0.8 | 0.5 | 0.3 | 0 | - | - | - | - |
| | | 48.4 | 3.3 | 3.0 | 2.7 | 2.5 | 2.2 | 1.9 | 1.7 | 1.4 | 1.1 | 1.3 | 1.1 | 0.8 | 0.5 | 0.3 | 0 | - | - | - |
| | | 48.8 | 3.5 | 3.3 | 3.0 | 2.7 | 2.5 | 2.2 | 1.9 | 1.7 | 1.4 | 1.6 | 1.3 | 1.1 | 0.8 | 0.5 | 0.3 | 0 | - | - |
| | | 49.2 | 3.8 | 3.5 | 3.3 | 3.0 | 2.7 | 2.5 | 2.2 | 1.9 | 1.7 | 1.9 | 1.6 | 1.3 | 1.1 | 0.8 | 0.5 | 0.3 | 0 | - |
| | | 49.6 | 4.1 | 3.8 | 3.5 | 3.3 | 3.0 | 2.7 | 2.5 | 2.2 | 1.9 | 2.1 | 1.9 | 1.6 | 1.3 | 1.1 | 0.8 | 0.5 | 0.3 | 0 |

この色の組み合わせはトレッド、ホイルベース数値が基準値よりの増減が大きい為、推奨外となります。

Bushing type sus-mount chart

| | | A | B | C | |
|------------------------------|----|---------|---------|---------|--------|
| 品番／Parts number | | B8-301A | B8-301B | B8-301C | |
| ブッシュの向き／Direction of Bushing | ○5 | ○5 | 39.5mm | 43.5mm | 46.4mm |
| | ○4 | ○4 | 39.9mm | 43.9mm | 46.8mm |
| | ○3 | ○3 | 40.3mm | 44.3mm | 47.2mm |
| | ○2 | ○2 | 40.7mm | 44.7mm | 47.6mm |
| | 1 | 1 | 41.1mm | 45.1mm | 48.0mm |
| | ○2 | ○2 | 41.5mm | 45.5mm | 48.4mm |
| | ○3 | ○3 | 41.9mm | 45.9mm | 48.8mm |
| | ○4 | ○4 | 42.3mm | 46.3mm | 49.2mm |
| | ○5 | ○5 | 42.7mm | 46.7mm | 49.6mm |

チームヨコモのお勧めセット（この数値を基準にスタートしてみて下さい。）

YD-4 : フロント0度（前後共にマウントAにブッシュ5番の39.5mm）

リヤ2.5度（前マウントBにブッシュ3番の44.3mm、後マウントCにブッシュ1番の48mm）

YD-2 : フロント0度（前後共にマウントAにブッシュ5番の39.5mm）

リヤ1.1度（前マウントBにブッシュ2番の45.5mm、後マウントCにブッシュ3番の47.2mm）