

サスマウント Suspension Mount		FF										RF											
		A										NA											
		#5	#4	#3	#2	#1	#2	#3	#4	#5	#5	#4	#3	#2	#1	#2	#3	#4	#5				
ブッシュ Bushing		内側/IN					—	外側/OUT					内側/IN					—	外側/OUT				
FR/RR	A	#5	39.5	0	-0.3	-0.5	-0.8	-1.1	-1.4	-1.6	-1.9	-2.2	2.7	2.5	2.2	1.9	1.6	1.4	1.1	0.8	0.5		
		#4	39.9	0.3	0	-0.3	-0.5	-0.8	-1.1	-1.4	-1.6	-1.9	3.0	2.7	2.5	2.2	1.9	1.6	1.4	1.1	0.8		
		#3	40.3	0.5	0.3	0	-0.3	-0.5	-0.8	-1.1	-1.4	-1.6	3.3	3.0	2.7	2.5	2.2	1.9	1.6	1.4	1.1		
		#2	40.7	0.8	0.5	0.3	0	-0.3	-0.5	-0.8	-1.1	-1.4	3.5	3.3	3.0	2.7	2.5	2.2	1.9	1.6	1.4		
		#1	41.1	1.1	0.8	0.5	0.3	0	-0.3	-0.5	-0.8	-1.1	3.8	3.5	3.3	3.0	2.7	2.5	2.2	1.9	1.6		
	A	#2	41.5	1.4	1.1	0.8	0.5	0.3	0	-0.3	-0.5	-0.8	4.1	3.8	3.5	3.3	3.0	2.7	2.5	2.2	1.9		
		#3	41.9	1.6	1.4	1.1	0.8	0.5	0.3	0	-0.3	-0.5	4.4	4.1	3.8	3.5	3.3	3.0	2.7	2.5	2.2		
		#4	42.3	1.9	1.6	1.4	1.1	0.8	0.5	0.3	0	-0.3	4.6	4.4	4.1	3.8	3.5	3.3	3.0	2.7	2.5		
		#5	42.7	2.2	1.9	1.6	1.4	1.1	0.8	0.5	0.3	0	4.9	4.6	4.4	4.1	3.8	3.5	3.3	3.0	2.7		