

# YZ44SF

## SETTING SHEET Ver.01

### CIRCUIT

- INDOOR  OUTDOOR  
 DIRT  ASTROTURF  CARPET  GLASS  WOOD  
 WET  DRY  DUSTY  SMOOTH  BUMPY  
 HARD PACKED  CLAY  BIUE GROOVE  \_\_\_\_\_  
 LOW TRACTION  MED TRACTION  HIGH TRACTION

DRIVER

DATE

### FRONT

◆CAMBER  ↔  \_\_\_\_\_ °  
 ◆TOE  IN  OUT \_\_\_\_\_ °  
 ◆RIDE HEIGHT \_\_\_\_\_ mm

OS4-200  
 OS-200A

8°  
 10°  
 12.5°  
 15°

4.3

FF  05  FR  01

Aluminum  
**SPRING**  
 ORANGE (YS-A750)  
 \_\_\_\_\_

**OIL**  
 # \_\_\_\_\_  
 1.6mmX2(BM-S162)  
 \_\_\_\_\_  
 \_\_\_\_\_ mm X \_\_\_\_\_  
 \_\_\_\_\_ mm X \_\_\_\_\_

### REAR

◆CAMBER  ↔  \_\_\_\_\_ °  
 ◆RIDE HEIGHT \_\_\_\_\_ mm

S4-008RL5

OZ2-415R  
 OZ2-415R00(Aluminum)

4.3

RF  05  RR  01

S  M  L

Aluminum  
**SPRING**  
 GREEN (YS-A1200)  
 \_\_\_\_\_

**OIL**  
 # \_\_\_\_\_  
 1.7mmX2(BM-S172)  
 \_\_\_\_\_  
 \_\_\_\_\_ mm X \_\_\_\_\_  
 \_\_\_\_\_ mm X \_\_\_\_\_

### DRIVE

F/# \_\_\_\_\_  
 R/# \_\_\_\_\_

F2  R2  
 F1  R1  
 F0  R0  
 R-0.5

# \_\_\_\_\_

MOTOR ⇨ \_\_\_\_\_ Rotor \_\_\_\_\_ mm  
 GEAR ⇨ Spur T / Pinion T : 2.6  
 BATTERY ⇨ \_\_\_\_\_  
 ESC  YOKOMO RPX  YOKOMO BL-PRO4  
 \_\_\_\_\_

Brace plate  
 YT-RW25 X \_\_\_\_\_  
 Chasis brace  
 Side plate

### TIRE

**FRONT**  
 TIRE ⇨ \_\_\_\_\_  
 INSERTS ⇨ \_\_\_\_\_  
 WHEELS ⇨ \_\_\_\_\_

**REAR**  
 TIRE ⇨ \_\_\_\_\_  
 INSERTS ⇨ \_\_\_\_\_  
 WHEELS ⇨ \_\_\_\_\_

### OTHER

### COMMENT

\_\_\_\_\_